This transparency is from last presentation: Realistic MC for the B

- Corrections and upgrades from previous sample:
 - Silicon noise correctly simulated
- of in 4.9.19 in Kay: internal degrees of freedom a ladder (bow, relative tilt) are not simulated out corrections are applied in Production
- In progress:
 - ✓ Full trigsim (in particular svtsim)
 - ✓ Event filtering based on trigsim


• Plan:

- Simulate multiple runs (eg. 150799: 3 pb⁻¹)
- Simulate multiple runs in the same job, weighted by their luminosity
- Complete validation on MCrun 142110 In progress
- Enter sample in DataFileCatalog
- Generate 1+svt test sample Waiting for sw
- ✓ Generate cc test sample


Realistic MC for the B

TrigSim included in runMC

- #include "XFTSim/XFTSim.hh"
- #include "XTRPSim/XTRPSimModule.hh"
- #include "svtsim/svtsimmodule.hh"
- //SDA for sytsim
- #include "L1GlobalTrigger/L1GlobalTriggerMaker.hh"
- #include "L2GlobalTrigger/L2SimModule.hh"
- //SDA for svtfilter
- #include "SemiLeptonicB/svtfilter.hh"
- #include "SemiLeptonicB/SimPrereq.hh"
- Event filtering has low efficiency:
 - 2% on simulated events (on "pi-pi" stream)
 - Simulation takes 38 s/evt → 1 evt/hour on a 700
 MHz pentium
- Need to adjust cuts at generator level and at GenTrig level to maximize efficiency and minimize bias.
- Sample of 100k bb with loose cuts is being produced now.
- CC sample produced (15k events)



Job 1



Job 2